## Declaration of performance

## for the product Optima Thermo Aquastop

1.	Unique identification code of the product-type						
	5905167778791 - Optima Thermo Aquastop						
Tvp	pe, batch or serial number or any other element allowing identifica	tion of the construction product as required under:					
2.	EAN	5 905 167 778 792					
	ended use or uses of the construction product, in accordance with t	the applicable harmonised technical specification, as fo					
3.	Insulating material for the acoustic use under floating floors	;					
<b>4</b> . Nar	me, registered trade name or registered trade mark and contact ac	ddress of the manufacturer as required pursuant:					
	Decora S.A. ; Prądzyńskiego 24a; 63-000 Środa Wielkopolska	a; Poland					
	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):						
	Not Applicable						
Syst	tem or systems of assessment and verification of constancy of perf	formance of the construction product as set out in Ann					
6.	System number - 4						
In c	case of the declaration of performance concerning a construction p	roduct covered by a harmonised standard					
7.	No synchronized standard						

8.	Declared performance					
Symbol	Parameter	Value		Unit	Norm	
Т	Thickness	1,5	+/- 0,15	[mm]	EN 823:2013	
L	Length	10000	-0% + 5%	[mm]	EN 822:2013	
W	Width	1000	-1% +2,5%	[mm]	EN 822:2013	
Q	Squareness	<5	0	[mm/m]	EN 824:2013	
S	Flatness	<2	0	[mm/m]	EN 825:2013	
AW	Surface mass	0,18	+/- 10%	[kg/m <sup>2</sup> ]	EN ISO 23997:2012	
QW	Density	[-]	[-]	[kg/m <sup>3</sup> ]	EN 1602	
RWS	Reflected walking sound	14	+/-2	[%]	CEN/TS 16354:2013, EPLF 021029-3	
IS	Impact sound improvement	18	+/-2	[dB]	EN ISO 10140:2007	
CS	Compressive strength at 0.5 mm compression	60	+/-10%	[kPa]	EN 826:2013	
CC	Static compressive strength	[-]	[-]	[kPa]	EN 1606:2013	
DL	Dynamic compressive strength	> 100 000		[cycles]	EN 13793:2014	
PC	punctual conformability	1,2	+/-10%	[mm]	EN ISO 868:2005	
TR	Thermal Resitance	0,033	+/- 0,005	[m <sup>2</sup> K/W]	EN 12664:2002	
SD	sD-value	>150		[m]	EN 12086:2013	
RLB	Resistance to Large Ball	≤ 1300		[mm]	EN 438-2:2016	
RTF	Reaction on fire	[-]		[-]	EN 13501-1:2010	

9.

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer

creation date	2020-08-13
modification date	2020-08-13
Printed	10.01.2022 13:44

almost the

🛯 🎸 Decoral