



## PURE OAK NARROW

Warm and nurturing this is oak in all its natural beauty. Pure oak narrow is a single-strip sleek oak floor from the Life Collection. A calm wood collection with few knots and an authentic look and feel. Four-sided microbevelling at the edges ensures a classic plank look. The innovative matt lacquer finish eliminates glare while protecting the wood from daily wear.

| PRODUCT DETAILS                                                                                 |                                             | FACTS                     |                     | TECHNICAL PROPERTIES           |             |               |
|-------------------------------------------------------------------------------------------------|---------------------------------------------|---------------------------|---------------------|--------------------------------|-------------|---------------|
| Article Number                                                                                  | LTCLRW3003-118                              | Wood Species              | Oak                 | Moisture                       | EN13183     | 7%±2%         |
| EAN Code                                                                                        | 7393969107433                               | Board                     | 1-strip             | content                        |             |               |
| Surface treatment                                                                               | Matt lacquer                                | Grading                   | Calm                | Minimun Mean Density kg/m³ >80 |             | >800 kg/m³    |
| Design features                                                                                 | Microbevelled 4-sided                       | Range                     | Kährs Life          | Reaction To<br>Fire            | EN13501-1   | Cfl-s1        |
| Dimensions                                                                                      | 1225 x 118 x 7 mm                           | Collection                | Life Collection     | Formaldehyde EN717-1           | E1          |               |
| Weight per Package x                                                                            | 10.9 kg                                     | Resandable                | Not resandable      | Emission                       | Emission    |               |
| Area per Package (m²)                                                                           | 1.74                                        | Natural/Stained           | Natural             | Content PCP                    | CEN/TR14823 | ≤ 5 x 10-6n   |
| Area per pallet (m²)                                                                            | 104.4                                       | Joint                     | Woodloc® 5G         | Breaking                       | EN1533      | NPD           |
| Package info                                                                                    | Packages may contain start and stop boards. | Floor heating             | Yes                 | Strength N/mm²                 |             |               |
|                                                                                                 |                                             | Warranty                  | 15 years            | Thermal                        | EN12664     | 0,134 W/mK    |
| DETAIL DESCRIPTION                                                                              |                                             | Wear-layer material       | Hardwood            | Conductivity                   |             |               |
| Even colour with minor variations. Small sized knots in limited numbers allowed.  COLOUR CHANGE |                                             | Wear-layer thickness      | 0.6 mm              | Thermal Resistance R-Value     |             | .0533 (m2K/W) |
|                                                                                                 |                                             | Core material             | HDF                 | Biological<br>Durability       | EN350-2     | Class 1       |
|                                                                                                 |                                             | Thickness                 | 7 mm                | CARB2                          |             | Compliant     |
| The colour matures over time                                                                    |                                             | Installation method       | Glue-down, Floating | Commercial                     | EN          | Class 33      |
|                                                                                                 |                                             | Resistance to indentation | >40 Newton/mm2      | usage<br>classification        | 14354:2017  | C1433 33      |

















## **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.