

# MANSFIELD

## WILD LUXURY COLLECTION

<b>CONSTRUCTION STRUCTURE STRUKTUR STRUKTURA</b>	Tufting 1/10" cut pile Tufté 1/10" cut pile Getuftet 1/10" cut Runo ciete tuftowane 1//10"	<b>IMPACT NOISE RATING ISOLATION PHONIQUE TRITTSCHALLVERBESSERUNG IZOLACJA AKUSTYCZNA</b>	EN ISO 10140-3 32 dB ΔLw
<b>PILE MATERIAL COMPOSITION DU VELOURS POLMATERIAL SKLAD RUNA</b>	100% PA	<b>SOUND ABSORPTION ABSORPTION PHONIQUE SCHALLABSORPTIONSGRAD ABSORBCJA DZWIEKU</b>	EN ISO 354 0,30 α W
<b>SECONDARY BACKING DOSSIER RÜCKEN PODKLAD</b>	Twin back	<b>THERMAL RESISTANCE RESISTANCE THERMIQUE WÄRMEDURCHLASSWIDERSTAND OPOR CIEPLNY</b>	ISO 8302 0,21 m² KW
<b>PILE WEIGHT POIDS DU VELOURS POLEINSATZGEWICHT WAGA RUNA</b>	± 2.300 gr/m²	<b>FASTNESS TO LIGHT SOLIDITE A LA LUMIERE LICHTECHTHEIT LICHT ODPORNOSC NA SWIATLO</b>	ISO 105-B02 ≥ 5-6
<b>TOTAL WEIGHT POIDS TOTAL GESAMTGEWICHT WAGA CALKOWITA</b>	± 2.800 gr/m²	<b>COLOUR FASTNESS TO WATER SOLIDITE A L'EAU WASSERECHEITHEIT DOPORNOSC KOLORU NA WODE</b>	EN ISO 105-E01 ≥ 4-5
<b>PILE THICKNESS EPAISSEUR DU VELOURS POLDICKE WYSOKOSC RUNA</b>	± 10,5 mm	<b>FIRE RESISTANCE COMPORTEMENT AU FEU BRENNVERHALTEN KLASA PALNOSCI</b>	EN 13501-1 C <sub>FL</sub> -s1 if glued
<b>TOTAL THICKNESS EPAISSEUR TOTALE GESAMTDICKE WYSOKOSC CALKOWITA</b>	± 13,5 mm	<b>WIDTH LARGEUR BREITE SZER</b>	EN ISO 3018 ca. 400 cm
<b>TUFT DENSITY NOMBRE DE POINTS NOPPENZAHL GESTOSC TUFTOWANIA</b>	± 273.000/m²		
<b>PRODIS / GUT</b>	5D2954AB		
<b>CLASSIFICATION CLASSEMENT KLASSIFIKATION KLASYFIKACJA</b>	EN 1307 23/32 - LC5		



ITC CO BV  
Kanegemstraat 15, B-8700  
Tielt itc-carpets.com

EN 14041
<b>CE</b>
19
ITC CO BV Kanegemstraat 15 - BE 8700 Tielt
DOP: 1011#IE00CV
Textile Floor Covering EN1307 Notified Body 2401
www.itc-carpets.com