

# ROSEFIELD

## WILD LUXURY COLLECTION

<b>CONSTRUCTION STRUCTURE</b> STRUKTUR STRUCTUUR	Tufting 5/64" cut pile Tufté 5/64" cut pile Getuftet 5/64" cut pile Runo ciete tuftowane 5/64"	<b>IMPACT NOISE RATING</b> ISOLATION PHONIQUE TRITTSCHALLVERBESSERUNG IZOLACJA SKUSTYCZNA	EN ISO 10140-3 31 dB ΔLw
<b>PILE MATERIAL</b> COMPOSITION DU VELOURS POLMATERIAL SKALD RUNA	100% PA	<b>SOUND ABSORPTION</b> ABSORPTION PHONIQUE SCHALLABSORPTIONSGRAD ABSORBCJA DZWIEKU	EN ISO 354 0,30 α W
<b>SECONDARY BACKING DOSSIER</b> RÜCKEN PODKLAD	Twin back	<b>THERMAL RESISTANCE</b> RESISTANCE THERMIQUE WÄRMEDURCHLASSWIDERSTAND OPR CIEPLNY	ISO 8302 0,15 m² KW
<b>PILE WEIGHT</b> POIDS DU VELOURS POLEINSATZGEWICHT WAGA RUNA	± 1.800 gr/m²	<b>FASTNESS TO LIGHT</b> SOLIDITE A LA LUMIERE LICHTECHTHEIT LICHTE ODPORNOSC NA SWIATLO	ISO 105-B02 ≥ 5-6
<b>TOTAL WEIGHT</b> POIDS TOTAL GESAMTGEWICHT WAGA CALKOWIAT	± 2.600 gr/m²	<b>COLOUR FASTNESS TO WATER</b> SOLIDITE A L'EAU WASSERECHTHEIT WATER ODPORNOSC KOLORU NA WODW	EN ISO 105-E01 ≥ 4-5
<b>PILE THICKNESS</b> EPAISSEUR DU VELOURS POLDICKE WYKOSC RUNA	± 8 mm	<b>FIRE RESISTANCE</b> COMPORTEMENT AU FEU BRENNVERHALTEN KLASA PALNOSCI	EN 13501-1 C <sub>FL</sub> -s1 if glued
<b>TOTAL THICKNESS</b> EPAISSEUR TOTALE GESAMTDICKE WYSOKOSC CALK	± 11 mm	<b>WIDTH</b> LARGEUR BREITE SZER	EN ISO 3018 ca. 400 cm
<b>TUFT DENSITY</b> NOMBRE DE POINTS NOPPENZAHL GESTOSC TIFTOWANIA	± 330.000/m²		
<b>PRODIS / GUT</b>	1C8B2DBE		
<b>CLASSIFICATION</b> CLASSEMENT KLASSIFIKATION KLASYFIKACJA	EN 1307 23/32 - LC5		



ITC CO BV  
Kanegemstraat 15, B-8700  
Tielt itc-carpets.com

EN 14041
19
ITC CO BV Kanegemstraat 15 - BE 8700 Tielt
DOP: 1011#IE00CV
Textile Floor Covering EN1307 Notified Body 2401
multicarpets.com