



## MANOR OAK

The powdery white stain on this single-strip oak floor from the Grande Collection softens its rustic expression and allows the blonde tones of the wood to come through. Each board is meticulously hand-scraped, which enhances the worn appearance of the floor. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Every board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. This product must be oiled after installation and prior to use.

### PRODUCT DETAILS

<b>Article Number</b>	201XABEKFVKE280
<b>Surface treatment</b>	Oil This floor should be oiled immediately after installation.
<b>Design features</b>	Bevelled 4-sided, Brushed, Handscraped
<b>Dimensions</b>	2800 x 260 x 20 mm
<b>Weight per Package</b>	38 kg
<b>Area per Package</b>	2.91 m <sup>2</sup>
<b>Area Per Board</b>	0.728 m <sup>2</sup>
<b>Package info</b>	Packages may contain start and stop boards.

### FACTS

<b>Wood Species</b>	Oak
<b>Board</b>	1-strip
<b>Grading</b>	Variation
<b>Range</b>	Kährs Supreme
<b>Collection</b>	Grande Collection
<b>Resandable</b>	2-4 times
<b>Natural/Stained</b>	Stained
<b>Joint</b>	Tongue & Groove
<b>Floor heating</b>	No
<b>Warranty</b>	30 years
<b>Wear-layer material</b>	Hardwood
<b>Wear-layer thickness</b>	5 mm
<b>Thickness</b>	20 mm
<b>Surface Colour</b>	White IFV

### TECHNICAL PROPERTIES

<b>TestMoistureContent</b>	7%±2%
<b>TestMinimunMeanDensity</b>	>500 kg/m <sup>3</sup>
<b>TestReactionToFire</b>	Dfl-s1
<b>TestFormaldehydeEmission</b>	E1
<b>TestContentPCP</b>	≤ 5 x 10 <sup>-6</sup> n
<b>TestBreakingStrength</b>	NPD
<b>TestThermalConductivity</b>	0,125 W/mK
<b>TestThermalResistanceRValue</b>	.16 (m <sup>2</sup> K/W)
<b>TestBiologDurability</b>	Class 1
<b>TestCarb2</b>	Compliant

### DETAIL DESCRIPTION

Naturally occurring wood colour variations allowed, from light to dark brown. The product includes large sound and black knots. Knots may vary in size and numbers. Grande products may continue to develop their rustic nature after the floor has been installed, splits and cracks that occur after installation are normal and should be considered part of the timbers natural character.

### COLOUR CHANGE

Stained product - noticeable color change over time.



**Descriptions & Imagery**

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*