KARTA INFORMACJI TECHNICZNEJ

Essentials 150

Wykładziny winylowe 2014

January 2014

Typ podłogi	**ISO 10582**	**Wykładzina winylowa**
Klasa użytkowa	**ISO 10874**	
	Klasa	21

Opis

ISO 24346 (EN 428)	**1,50 mm**	
ISO 24340 (EN 429)	**0,15 mm**	
ISO 24341 (EN 426)	**35 m** **4+3+2m**	
ISO 23997 (EN 430)	**1,210 kg/m²**	

EN 660-2 Grupa ścieralności	**T**
ISO 4918 (EN 425) Odporność na działanie kółek krzeseł	**NO**
EN ISO 717/2 Absorbcja dźwięków	**ca. 12 dB**
ISO 24343-1 (EN 433) Wgniecenie resztkowe	**≤ 0,35mm**

Pozostałe cechy

ISO 105/B02 Trwałość kolorów	**≥ 6**	
ISO 23999 (EN 434) Stabilność wymiarów	**≤ 0,40 %**	
ISO 10456 (EN 12524) Odporość termiczna Ogrzewanie podłogowe	**0,02 m²/kW**	

Antypoślizgowość EN 13893 DIN 51130	**μ ≥ 0,30** **R10**	
Przetwarzalność	**OK**	
Odporność chemiczna	**OK**	

Ognioodporność EN 13501-1 Report N° :	**Bfl-s1** **RA10-0254**	
EN 1815 Elektrostatyczność	**≤ 2 kV**	

Essentials 150
No. 0004-0027-DoP-2013-04
http://www.home.tarkett.com
Manufactured by: Tarkett Holding GmbH - 122, Granastrasse 54329 Konz, Germany
EN 14041:2004

EXCLUSIVE 200 | 100 % Recyclable | PHTHALATE FREE Technology* *except recycled content | <100µg/m³ Better Indoor Air Quality *TVOC AT 28 DAYS | ÉMISSIONS DANS L'AIR INTÉRIEUR A+ (A+ A B C)

Although the ulmost care is taken, the data here given could be imprecise and liable to modifications of a technical nature. In its strive to improve its floor solutions, Tarkett reserves the right to modify their tehcnical specifications, colours and materials at any moment and wthout prior notice.