

PRODUCT DATA SHEET

# SUPER S

May 2014

<b>Type of flooring</b>	<b>EN 653</b>	<b>Resilient Residential PVC floor covering</b>
<b>Class of use</b>	<b>ISO 10874</b>	
	<b>Class</b>	<b>23</b>

Description



	<b>ISO 24346</b>	<b>3,00 mm</b>		<b>ISO 24341</b>	<b>30m (15-30)</b> Length + Width <b>2,5/3/3,5/4m</b>
	<b>ISO 24340</b>	<b>0,25 mm</b>		<b>ISO 4918</b>	<b>Very good</b> Castor chair
	<b>prEN 660-1</b>	<b>T</b> Abrasion group		<b>ISO 717/2</b>	<b>19 dB</b> Impact sound absorption
	<b>ISO 23997</b>	<b>1,90 kg/m<sup>2</sup></b>		<b>ISO 24343-1</b>	<b>≤ 0,35 mm</b> Residual indentation

Optional Characteristics

	<b>ISO 105/B02</b>	<b>7/8</b> Light fastness		<b>Recyclable</b>	<b>OK</b>		<b>Fire Classification</b> EN 13501-1 Report N° : <b>Bfl-s1</b> <b>RA08-0414</b>
	<b>ISO 23999</b>	<b>&lt; 0,1 %</b> Dimensional stability					<b>Fungi and bacteria resistance:</b> Does not contribute to infection spreading
	<b>DIN 52612</b>	<b>0,03 - 0,04 m<sup>2</sup> k/W</b> Thermal resistance					



Manufactured in Serbia by TARKETT

EN 14041 : 2004