

QUALITY
ORDER CODE

DATE: **3/05/2019**
REPLACES: 21/12/2017

WIDTH (±) cm
TYPE
GAUGE AND TYPE
TEXTURING
DYEING/PRINT METHOD

PILE COMPOSITION
FIBRE BRAND
WOOLMARK
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m²
TOTAL WEIGHT (±) gr/m²

EFFECTIVE PILE HEIGHT (±) mm
TOTAL HEIGHT (±) mm
NUMBER OF KNOTS (±) m²
STITCHES OVER WIDTH (±) / 10 cm
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m
PILE IN/OUT

LANO CLASSIFICATION

BEDROOM
LIVING ROOM
OFFICE
CASTOR ROLLCHAIRS DOMESTIC USE
CASTOR ROLLCHAIRS PROFESSIONAL USE
STAIRS DOMESTIC USE
STAIRS PROFESSIONAL USE
ELECTROSTATIC BEHAVIOUR
UNDERFLOOR HEATING
BATH ROOM
NON-FRAY
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER
DIBT

UPEC n°
CLASSIFICATION

HQE
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION
CLASSIFICATION BS7131

PLEASURE KT
PLE

± 400 & 500
COLLECTION
5/64" SAXONY

PIECE DYED

PA 6.6

WOVEN

TEXTILE BACKING C-BACK

± 1 870
± 3 090

± 9,0
± 11,5
± 262.080
± 50,40
± 52,00

±
±

± 25
PILE IN

✓
✓
✓
✓
✓
✓

ANTISTATIC
✓

8E3CBB7F

Cl. 32
Commercial General



LC5



Bfl-s1





QUALITY

IMPACT SOUND INSULATION	(±) dB	ISO 140/8
THERMAL RETENTION	(±) m ² /KW	ISO 8302
TOG rating	(±)	
PERMANENTLY ANTISTATIC	(±) volt	ISO 6356
LIGHTFASTNESS		ISO 105-B02
RUBBINGFASTNESS DRY		ISO 105 X12
RUBBINGFASTNESS WET		ISO 105 X12
WATERFASTNESS CHANGE IN COLOUR		ISO 105-E01
WATERFASTNESS STAINING		ISO 105-E01

PLEASURE KT

± 25	
± 0,134	
± 1,34	
≤ 2000	
≥ 5	
≥ 3-4	
≥ 3	
≥ 3-4	
≥ 2-3	

LABEL CE


 18 EN 14041
 DOP 1038-125395
 NB 1611

 LANO NV - Venetiëlaan 33
 B-8530 HARELBEKE
 Floor carpets to use in
 buildings

RECOMMENDED INSTALLATION

ALL-OVER STICK DOWN WITH EC1 APPROVED ADHESIVE - SHORT PIN MUSHROOM TAPE

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

AVAILABLE FROM

AVAILABLE FROM

COLOURS

<u>KT 400</u>	PLE	<u>KT 500</u>
020	LAVENDER	020
040	ANEMONE	040
180	RUM	180
220	ACORN	220
240	CREAM	240
250	MAGNOLIA	250
260	CAMEL	260
620	SAVANNA	620
760	WEDGWOOD	760
780	STEEL	780
810	CHARCOAL	810
820	SLATE	820
830	ASH	830
840	MOONSHINE	840
860	GRANITE	860
880	PEARL	880

<u>KT 400</u>	PLE	<u>KT 500</u>



WE RESERVE THE RIGHT TO ALTER TECHNICAL SPECIFICATIONS WITHOUT PRIOR NOTICE