


CONSTRUCTION	Tufting 1/10" loop pile	STAIR SUITABILITY	EN 1963
STRUCTURE	Tufté 1/10" bouclé	ESCALIERS	A: intensive use
STRUKTUR	Getuftet 1/10" Schlinge	STOSOWANIE NA	
STRUKTURA	Getuft 1/10" lussenpool	SCHODACH	
PILE MATERIAL	100% PA 6 IMPREL®	PERMANENTLY ANTISTATIC	ISO 6356
COMPOSITION DU VELOURS		ANTISTATIQUE PERMANENT	< 2 kV
POLMATERIAL		PERMANENT ANTISTATISCH	
MATERIAL		ANTYSTATYKA	
PRIMARY BACKING	Non Woven PES	IMPACT NOISE RATING	ISO 140-8
SUPPORT	Non tissé PES	ISOLATION PHONIQUE	25 dB ΔLw
TRÄGERMATERIAL	Vlies, PES	TRITTSCHALLVERBESSERUNG	
PODKLAD PIERWOTNY	Vilt, PES	TLUMIENIE HALASU	
SECONDARY BACKING	Action back	SOUND ABSORPTION	ISO 354
DOSSIER		ABSORPTION PHONIQUE	0,15 αw
RÜCKEN		SCHALLABSORPTIONSGRAD	
PODKLAD		ABSORPCJA DZWIEKU	
PILE WEIGHT	Ca. 640 gr/m ²	THERMAL RESISTANCE	ISO 8302
POIDS DU VELOURS		RÉSISTANCE THERMIQUE	0,07 m ² KW
POLEINSATZGEWICHT		WÄRMEDURCHLASSWIDERSTAND	
WAGA RUNA		OPORNOSC CIEPLNA	
TOTAL WEIGHT	Ca. 1.711 gr/m ²	FASTNESS TO LIGHT	ISO 105-B02
POIDS TOTAL		SOLIDITÉ A LA LUMIÈRE	≥ 5-6
GESAMTGEWICHT		ODPORNOSC	
WAGA CALK		NA SWIATLO	
PILE HEIGHT	Ca. 3,1 mm	COLOUR FASTNESS TO WATER	EN ISO 105-E01
EPAISSEUR DU VELOURS		ODPORNOSC	≥ 4-5
POLHÖHE		KOLORU NA	
WYS RUNA		WODE	
TOTAL HEIGHT	Ca. 5,8 mm	FIRE RESISTANCE	EN 13501-1
EPAISSEUR TOTAL		COMPORTEMENT AU FEU	Cfl-s1
GESAMTHÖHE		BRENNVERHALTEN	
WYS CALK		KLASA PALNOSCI	
TUFT DENSITY	Ca. 218.400/m ²	RUBBING FASTNESS	EN ISO 105-X12
NOMBRES DE POINTS		SOLIDITÉ AU FROTTEMENT	≥ 4
GESTOSC		ODPORNOSC	
TUFTOWANIA		NA SCIERANIE	
PILE DENSITY	Ca. 0,118 g/cm ³	WIDTH	EN ISO 3018
DENSITÉ DU VELOURS		LARGEUR	ca. 400 cm
POLROHDICHTE		BREITE	
GESTOSC RUNA		SZER	
CLASSIFICATION	EN 1307	DESIGN REPEAT CM	ca. 196 (W) x
CLASSEMENT	33 - LC1	RACCORD CM	ca. 295 (H)
KLASSIFIKATION		RAPPORT CM	
KLASYFIKACJA		RAPORT CM	
CASTOR CHAIR SUITABILITY	EN 985		
CHAISE À ROULETTES	A: intensive use		
STUHLROLLENEIGNUNG			
KRZESLA NA KOLKACH			



EN14041




15

ITC CO BV
Kanegemstraat 15 - BE 8700 Tielt

DOP: 1011#IEOACL

Textile Floor Covering EN1307
Notified body 0493



my.itc-carpets.com

EAC



REG. NR
D40C4B0A
www.pro-dis.info





↔ ca. 196 x ↕ ca. 295 cm



▲ 93



▲ 99



▲ 14



▲ 27



▲ 32



▲ 43



▲ 45



▲ 98



▲ 79



▲ 39